Proven Tillage Equipment



OzValue AG MACHINERY

ILGI manufacture a wide range of tillage options. They offer tillage equipment capable of various tillage tasks, from light soil tilth and stubble preparation through to complete primary cultivation.

These proven machines are available in a wide range of sizes, providing your farm with the perfect machine suitable for a wide range of tractor power options.

Several working widths are available, from 2 metres through to 6 metres (folding to a narrow 2.8 m for easy transport), plus machine options like fixed or trailing drawbar, with standard cage roller or more aggressive disc roller options.

ILGI is your most efficient and cost-effective tillage option.

Explore the ILGI Tillage Range



Megastar Rigid Offset Discs



Aragon Linkage Rigid Disc Tillers



Aragon Linkage Folding Disc Tillers



Megastar-K Folding Offset Discs



Texas Compact Disc Tiller



Aragon Trailing Folding Disc Tillers





Scan to view online or visit **ozvalueag.com.au**





OzValueAG Australia

f 🕑 🖸

6 Wiltshire Lane, Delacombe (Ballarat) VIC 3350 P. 03 5335 8181 E. sales@ozvalueag.com.au



"We're farmers too"

We know more than ever, farming in Australia has become highly dependent on machinery cost and reliability.

This is why OzValue AG we're committed to bringing the farmers of Australia, well priced quality machinery.

We are working farmers ourselves and fully understand what's required from modern farm machinery. Our team continues to design and source robust machinery from quality manufacturers around the world. We then sell direct to the farmer, eliminating importers and distributors and their added costs.

This simply results in a lower price for you, the farmer.



OzValue AG Queensland

103 River Rd. Kingaroy QLD 4610 P. 07 4162 2100 E. qld@ozvalueag.com.au



ozvalueag.com.au

ILGI Megastar Offset Discs

MEGA TOUGH, **MEGA STRONG.**

Megastar, the Heavy Duty Frame Offset Disc Harrow. Manufactured in various sizes from 18 to 36 discs without folding wings, and from 40 to 60 discs with folding wings.

Standard with 660 mm discs, further options including 220 mm disc spaces and plain or notched type discs. These alternatives enable farmers to choose the most suitable equipment for their own conditions. The disc direction angle can be opened to a maximum of 22 degrees to achieve excellent soil working and depth.

ILGI Megastar Offset Discs are rigid frame harrows with easy angle adjustment, strong 42mm² steel shaft, heavy duty adjustable scraper, side discs, standard pintle hitch and easy levelling.







Megastar Rigid Offset Specifications

Models	24	28	32	36		
Number of Discs	24	28	32	36		
Disc Diameter	660 mm	660 mm	660 mm	660 mm		
Working Width	2600 mm	3000 mm	3400 mm	3800 mm		
Weight	1980 kg	2145 kg	2460 kg	2700 kg		
Power^	90-100 hp	110-120 hp	130-140 hp	150-160 hp		
Disc Spacing	230 mm	230 mm	230 mm	230 mm		
*Specs are approximate and subject to change. ^Power Requirement may vary depending on soil conditions.						



Megastar Features

Heavy Duty Bearings



Cast iron bearing casings with double 6215 ball bearings and 50x80x13 double seals inside.

Hydraulic Gang Adjustment



Adjustable angle for easy adjustment of working depth, overturn and hackling whilst working with the hydraulic system.

Robust Adjustable Scrapers



Steel chassis, standard disc concavity & sizes. Can be worked on all soil conditions due to its robust structure.

Adjustable Drawbar



Adjustable pull type hitch ensures safe transport on the road and solid pulling of the machine when working in the field.

"We're farmers too"





Hydraulic Gang Option Available

Megastar-K Folding Offset Specifications

Models	40	48	56	60
Number of Discs	40	48	56	60
Disc Diameter	660 mm	660 mm	660 mm	660 mm
Working Width	4200 mm	5000 mm	5800 mm	6200 mm
Weight	3650 kg	3990 kg	4330 kg	4515 kg
Power^	150-160 hp	180-200 hp	230-250 hp	270-290 hp
Disc Spacing	230 mm	230 mm	230 mm	230 mm

*Specs are approximate and subject to change. ^Power Requirement may vary depending on soil conditions.

Easy Front to Rear Levelling



Uniform front to rear soil penetration. Sprung rigger arm between shaft and drawbar provides even furrows and minimises both bearing and disc wear.

Robust & Durable Frame



Frame is composed from strong 100x200x6mm steel section. Its strong structure is designed to deal with the hardest of soil conditions.

Strong Steel Shaft



40mm diameter high carbon steel shaft Steel spacers that are highly resistant pin with adjustable torque.

Steel Spacers



to breaking and shock.

Megastar-K Exclusive Features

Easy Folding Mechanism



Outer gangs hydraulically fold for easy transport.





Each wing has a secondary securing pin to ensure safe and secure transport.

